



Scapewel Models

| Model | Inside Width | Depth | Height | Maximum width of opening | | Cover Models | Suggested Window Size | |
|---------|--------------|-------|--------|--------------------------|------------|--------------|-----------------------|-------------|
| | | | | Wall mount | Buck mount | | Width | Max. Height |
| 4048-42 | 42" | 41" | 48" | 42" | 38" | 4042 | 36" | 40.5" |
| 4048-54 | 54" | 41" | 48" | 54" | 50" | 4054 | 48" | 40.5" |
| 4048-66 | 66" | 41" | 48" | 66" | 62" | 4066 | 60" | 40.5" |
| 4862-42 | 42" | 49" | 62" | 42" | 38" | 4842 | 36" | 54.5" |
| 4862-54 | 54" | 49" | 62" | 54" | 50" | 4854 | 48" | 54.5" |
| 4862-66 | 66" | 49" | 62" | 66" | 62" | 4866 | 60" | 54.5" |

| SPECIFICATIONS | | WINDOW WELL SYSTEM BILCO SCAPEWEL | |
|---|--|---|--|
| Construction: HDPE plastic w/ foam core | | Woodard's Concrete Products, Inc. 629 Lybolt Road, Bullville, NY 10915 (845) 361-3471 / Fax 361-1050 | |
| Satisfies Section R310.2 of the 2000 IRC for emergency escape window wells | | | |
| Your Window requirements: min. 5.7 sq foot clear opening (20"w & 24"h min.) | | | |
| | | Page 3E 8/11/10 | |